

maxon motor control's EPOS4 products are small-sized, full digital, smart positioning control units. Their high power density allows flexible use for brushed DC and brushless EC (BLDC) motors up to approximately 750 Watts with various feedback options, such as Hall sensors, incremental encoders as well as absolute sensors in a multitude of drive applications.

EPOS4 controllers are specially designed to be commanded and controlled as a slave node in the CANopen network. In addition, the units can be operated via any USB or RS232 communication port of a Windows or Linux workstation. Moreover, the integrated extension interface allows optional communication interfaces, such as EtherCAT or other additional functionalities.

Latest technology, such as field-oriented control (FOC) and acceleration/velocity feed forward in combination with highest control cycle rates allow sophisticated, ease-of-use motion control.

**Legend:** ✓ = included / nnnnnn = order number / \*\* = available shortly / (a) requires an optionally available extension card (see "Accessories" on page 6) / (b) optional for separate logic supply / (c) mandatory for supply of power stage



	EPOS4 Module 24/1.5 (536630)	EPOS4 Compact 24/1.5 CAN (546714)	EPOS4 50/5 (546047)	EPOS4 Module 50/5 (534130)	EPOS4 Compact 50/5 CAN (541718)	EPOS4 Module 50/8 (504384)	EPOS4 Compact 50/8 CAN (520885)	EPOS4 Module 50/15 (504383)	EPOS4 Compact 50/15 CAN (520886)
<b>Communication Interfaces</b>									
CANopen Slave	max. 1 Mbit/s								
CANopen Application Layer and Communication Profile	CiA 301								
CANopen Layer Setting Services and Protocol (LSS)	CiA 305**								
CANopen Device Profile Drives and Motion Control	CiA 402								
USB 2.0 / USB 3.0	Full speed								
Gateway function USB-to-CAN	✓								
RS232	max. 115'200 bit/s								
Gateway function RS232-to-CAN	✓								
EtherCAT Slave (IEC 61158)	max. 100 Mbit/s (100 Base Tx)								
	✓ (a)**	—	✓ (a)**	✓ (a)**	—	✓ (a)**	—	✓ (a)**	—
<b>Motors</b>									
Brushed DC motors up to (continuous / max.)	36 W / 108 W	36 W / 108 W	250 W / 750 W	250 W / 750 W	250 W / 750 W	400 W / 1'500 W	400 W / 1'500 W	750 W / 1'500 W	750 W / 1'500 W
Brushless EC motors (BLDC) up to (continuous / max.)	36 W / 108 W	36 W / 108 W	250 W / 750 W	250 W / 750 W	250 W / 750 W	400 W / 1'500 W	400 W / 1'500 W	750 W / 1'500 W	750 W / 1'500 W
<b>Sensors (Feedback)</b>									
Digital Hall sensors (EC motors)	✓								
Digital incremental encoder (2-/3-channel, single-ended or differential)	✓								
Analog incremental encoder (3-channel, sin/cos, differential)	✓**								
SSI absolute encoder (configurable)	✓								
BiSS C absolute encoder (configurable)	✓ (a)**	—	✓ (a)**	✓ (a)**	—	✓ (a)**	—	✓ (a)**	—
EnDat 2.2 absolute encoder (configurable)	✓ (a)**	—	✓ (a)**	✓ (a)**	—	✓ (a)**	—	✓ (a)**	—
<b>Commutation</b>									
Digital Hall sensors	✓								
Digital Hall sensors + digital incremental encoder	✓								
Digital Hall sensors + analog incremental encoder	✓**								
Digital Hall sensors + absolute encoder	✓								
Absolute encoder	✓								

	EPOS4 Module 24/1.5 (536630)	EPOS4 Compact 24/1.5 CAN (546714)	EPOS4 50/5 (546047)	EPOS4 Module 50/5 (534130)	EPOS4 Compact 50/5 CAN (541718)	EPOS4 Module 50/8 (504384)	EPOS4 Compact 50/8 CAN (520885)	EPOS4 Module 50/15 (504383)	EPOS4 Compact 50/15 CAN (520886)
<b>Electrical Data</b>									
Nominal power supply voltage (+V <sub>CC</sub> )	10...24 VDC	10...24 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC
Nominal logic supply voltage (+V <sub>C</sub> )	10...24 VDC	10...24 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC
Absolute supply voltage limits (+V <sub>min</sub> / +V <sub>max</sub> )	8 VDC / 28 VDC	8 VDC / 28 VDC	8 VDC / 56 VDC	8 VDC / 56 VDC	8 VDC / 56 VDC	8 VDC / 56 VDC	8 VDC / 56 VDC	8 VDC / 56 VDC	8 VDC / 56 VDC
Output voltage (max.)	0.9 x +V <sub>CC</sub>								
Output current (I <sub>cont</sub> / I <sub>max</sub> )	1.5 A / 4.5 A (<30 s)	1.5 A / 4.5 A (<30 s)	5 A / 15 A (<15s)	5 A / 15 A (<3 s)	5 A / 15 A (<3 s)	8 A / 30 A (<5 s)	8 A / 30 A (<5 s)	15 A / 30 A (<60 s)	15 A / 30 A (<60 s)
Pulse width modulation frequency	100 kHz	100 kHz	50 kHz	50 kHz	50 kHz	50 kHz	50 kHz	50 kHz	50 kHz
Sampling rate PI current controller	25 kHz (40 μs)								
Sampling rate PID speed controller	2.5 kHz (400 μs)								
Sampling rate PID positioning controller	2.5 kHz (400 μs)								
Max. efficiency	89%	89%	98%	97%	97%	98%	98%	98%	98%
Max. speed DC motor	limited by max. permissible speed (motor)								
Max. speed EC motor, block commutation	100'000 rpm (1 pole pair)								
Max. speed EC motor, sinusoidal commutation	50'000 rpm (1 pole pair)								
Built-in motor choke	—	3 x 94 μH; 1.5 A	3 x 15 μH; 5 A	—	3 x 9.4 μH; 5 A	—	3 x 2.2 μH; 15 A	—	3 x 2.2 μH; 15 A
<b>Inputs / Outputs</b>									
Digital Hall sensor signals	H1, H2, H3 (+2...+24 VDC, internal pull-up)								
Digital incremental encoder signals	A, A\, B, B\, I, I\ (EIA RS422, 6.25 MHz)								
Encoder signals	A, A\, B, B\, I, I\ (EIA RS422, 6.25 MHz) Clock, Clock\ Data, Data\ Digital incremental, analog incremental**, absolute serial SSI, BiSS (a), EnDat (a)								
Digital inputs	4 (+2.1...+36 VDC) all Modules all Compacts and housing versions								
Digital outputs	2 (open collector, max. 36 VDC / 500 mA, internal pull-up)								
High-speed digital inputs	4 (EIA RS422, 6.25 MHz)								
High-speed digital outputs	1 (EIA RS422, 6.25 MHz)								
Analog inputs	2 (resolution 12-bit, -10...+10 V, 10 kHz, differential)								
Analog outputs	2 (resolution 12-bit, -4...+4 V, 25 kHz)								
STO inputs	2 (+4.5...+30 VDC, optically isolated)								
STO outputs	1 (max. 30 VDC / 15 mA, optically isolated with self-resetting short-circuit protection)								
Sensor supply voltage	+5 VDC (I <sub>L</sub> ≤100 mA)								
Auxiliary output voltage	+5 VDC (I <sub>L</sub> ≤150 mA)								
Status indicators (LEDs or bi-color LEDs)	Device status	Device status	Device status	Device status	Device status	Device status	Device status	Device status	Device status
	—	—	NET status	—	—	—	—	—	—
	—	—	NET port	—	—	—	—	—	—

	EPOS4 Module 24/1.5 (536630)	EPOS4 Compact 24/1.5 CAN (546714)	EPOS4 50/5 (546047)	EPOS4 Module 50/5 (534130)	EPOS4 Compact 50/5 CAN (541718)	EPOS4 Module 50/8 (504384)	EPOS4 Compact 50/8 CAN (520885)	EPOS4 Module 50/15 (504383)	EPOS4 Compact 50/15 CAN (520886)
<b>Connections</b>									
X1 Power Supply	Box header (1.27 mm), 2x23 poles	—	Molex Mini-Fit Jr., 2 poles	Box header (1.27 mm), 2x23 poles	—	Pin header (2.54 mm), 2x16 poles	Molex Mega-Fit, 2 poles	Pin header (2.54 mm), 2x16 poles	Molex Mega-Fit, 2 poles
X2 Logic Supply		—	Molex Mini-Fit Jr., 2 poles		—		Molex Mini-Fit Jr., 2 poles		
X1/X2 Power & Logic Supply		Harting har-flexicon, 3 poles	—		Harting har-flexicon, 3 poles		—		
X3 Motor		—	Molex Mini-Fit Jr., 4 poles		—		Molex Mini-Fit Jr., 4 poles		
X3a Motor ( $I_{cont} \leq 11$ A)		—	—		—		Molex Mini-Fit Jr., 4 poles		
X3b Motor ( $I_{cont} \leq 15$ A)		—	—		—		—		
X3c Motor		Hirose DF3DZ, 3 poles	—		—		—		
X3a/X4a Motor & Hall Sensor		Harting har-flexicon, 8 poles	—		—		—		
X3b/X4b Motor & Hall Sensor		Lumberg Minimodul 8 poles	—		—		—		
X4 Hall Sensor		—	Molex Micro-Fit 3.0, 6 poles		—		Molex Micro-Fit 3.0, 6 poles		
X5 Encoder	Pin header 2.54 mm, 2x5 poles	Pin header 2.54 mm, 2x5 poles	—	Pin header 2.54 mm, 2x5 poles	—	Pin header 2.54 mm, 2x5 poles	—	Pin header 2.54 mm, 2x5 poles	
X6 Sensor	Box header (1.27 mm), 2x23 poles	Molex CLIK-Mate, 2x5 poles	Molex CLIK-Mate, 2x5 poles	Box header (1.27 mm), 2x23 poles	Molex CLIK-Mate, 2x5 poles	Pin header (2.54 mm), 2x23 poles	Molex CLIK-Mate, 2x5 poles	Pin header (2.54 mm), 2x23 poles	Molex CLIK-Mate, 2x5 poles
X7 Digital I/O		Molex CLIK-Mate, 8 poles	Molex CLIK-Mate, 8 poles		Molex CLIK-Mate, 8 poles		Molex CLIK-Mate, 8 poles		
X8 Analog I/O		Molex CLIK-Mate, 7 poles	Molex CLIK-Mate, 7 poles		Molex CLIK-Mate, 7 poles		Molex CLIK-Mate, 7 poles		
X9 STO		Molex CLIK-Mate, 8 poles	Molex CLIK-Mate, 8 poles		Molex CLIK-Mate, 8 poles		Molex CLIK-Mate, 8 poles		
X10 RS232		Molex CLIK-Mate, 5 poles	Molex CLIK-Mate, 5 poles		Molex CLIK-Mate, 5 poles		Molex CLIK-Mate, 5 poles		
X11 CAN 1		Molex CLIK-Mate, 4 poles	Molex CLIK-Mate, 4 poles		Molex CLIK-Mate, 4 poles		Molex CLIK-Mate, 4 poles		
X12 CAN 2		Molex CLIK-Mate, 4 poles	Molex CLIK-Mate, 4 poles		Molex CLIK-Mate, 4 poles		Molex CLIK-Mate, 4 poles		
X13 USB	USB Type micro B, female								
X14 Extension NET IN (a)	—	—	RJ45 10/100-BASE-TX	—	—	—	—	—	—
X15 Extension NET OUT (a)	—	—	RJ45 10/100-BASE-TX	—	—	—	—	—	—
X16 Extension Signal (a)	—	—	Molex CLIK-Mate, 2x5 poles	—	—	—	—	—	—
<b>Mechanical Data</b>									
Weight (approximate)	17 g	58 g	206 g	17 g	58 g	23 g	86 g	70 g	126 g
Dimensions (L x W x H)	53.8 x 38.8 x 11.1 mm	55.0 x 40.0 x 31.1 mm	105.0 x 83.0 x 38.7 mm	53.8 x 38.8 x 11.1 mm	55.0 x 40.0 x 31.1 mm	59.5 x 46.0 x 14.1 mm	59.5 x 58.5 x 33.0 mm	59.5 x 62.0 x 16.4 mm	59.5 x 65.5 x 35.1 mm
Mounting	Pluggable (female head- ers 1.27 mm) or M2.5 screws	M2.5 screws	M4 screws	Pluggable (female head- ers 1.27 mm) or M2.5 screws	M2.5 screws	Pluggable (female head- ers 2.54 mm) or M2.5 screws	M2.5 screws	Pluggable (female head- ers 2.54 mm) or M3 screws	M3 screws
<b>Environmental Conditions</b>									
Temperature – Operation	-30...+60 °C	-30...+45 °C	-30...+50 °C	-30...+45 °C	-30...+25 °C	-30...+45 °C	-30...+45 °C	-30...+25 °C	-30...+25 °C
Temperature – Extended range and derating	+60...+73 °C -0.115 A/°C	+45...+70 °C -0.060 A/°C	+50...+80 °C -0.167 A/°C	+45...+75 °C -0.167 A/°C	+25...+70 °C -0.111 A/°C	+45...+77 °C -0.250 A/°C	+45...+77 °C -0.250 A/°C	+25...+77 °C -0.288 A/°C	+25...+77 °C -0.288 A/°C
Temperature – Storage	-40...+85 °C								
Altitude – Operation	0...6'000 m MSL								
Altitude – Extended range	6'000...10'000 m MSL (for derating see Hardware Reference)								
Humidity (condensation not permitted)	5...90%								

	EPOS4 Module 24/1.5 (536630)	EPOS4 Compact 24/1.5 CAN (546714)	EPOS4 50/5 (546047)	EPOS4 Module 50/5 (534130)	EPOS4 Compact 50/5 CAN (541718)	EPOS4 Module 50/8 (504384)	EPOS4 Compact 50/8 CAN (520885)	EPOS4 Module 50/15 (504383)	EPOS4 Compact 50/15 CAN (520886)
<b>Directives &amp; Standards</b>									
Generic	IEC/EN 61000-6-2; IEC/EN 61000-6-3								
Applied	IEC/EN 55022 (CISPR22); IEC/EN 61000-4-3; IEC/EN 61000-4-4; IEC/EN 61000-4-6								
Environment	IEC/EN 60068-2-6; MIL-STD-810F								
Safety (UL File Number; unassembled PCB)	E207844	E207844	E229342	E207844	E207844	E76251; E207844; E337862	E76251; E116354; E207844; E337862	E76251; E207844; E337862	E76251; E116354; E207844; E337862
Reliability (MIL-HDBK-217F; MTBF)	611'610 hours	326'977 hours	296'741 hours	314'822 hours	253'865 hours	245'451 hours	210'109 hours	240'400 hours, with heat sink <3.1 K/W	199'049 hours, with heat sink <3.1 K/W
<b>Functionality</b>									
<b>Operating Modes</b>									
CST Cyclic Synchronous Torque Mode	✓								
CSV Cyclic Synchronous Velocity Mode	✓**								
CSP Cyclic Synchronous Position Mode	✓**								
PVM Profile Velocity Mode	✓								
PPM Profile Position Mode	✓								
IPM Interpolated Position Mode	✓**								
HMM Homing Mode	✓								
Master Encoder Functionality	✓**								
Step/Direction Functionality	✓**								
Analog Set Value Functionality	✓**								
<b>Features</b>									
Feed forward (acceleration/velocity for inertia and friction compensation)	✓								
Field-oriented Control (FOC)	✓								
Velocity observer	✓								
Standalone programmability	✓**								
Advanced automatic control settings (Auto Tuning)	✓								
Safe Torque Off (based on IEC/EN 61800-5-2, certification pending)	✓								
<b>Digital I/O Functionality</b>									
Inputs (configurable)	✓								
Touch Probe	✓**								
Reference switches	✓								
Limit switches	✓								
Quickstop	✓								
Drive Enable	✓								
General purpose	✓								
Outputs (configurable)	✓								
Position Compare	✓**								
Holding Brake	✓								
Ready/Fault	✓								
General purpose	✓								

	EPOS4 Module 24/1.5 (536630)	EPOS4 Compact 24/1.5 CAN (546714)	EPOS4 50/5 (546047)	EPOS4 Module 50/5 (534130)	EPOS4 Compact 50/5 CAN (541718)	EPOS4 Module 50/8 (504384)	EPOS4 Compact 50/8 CAN (520885)	EPOS4 Module 50/15 (504383)	EPOS4 Compact 50/15 CAN (520886)
<b>Analog I/O Functionality</b>									
Inputs (configurable)					✓				
Analog set value					✓**				
General purpose					✓				
Outputs (configurable)					✓**				
Current monitor					✓**				
Velocity monitor					✓**				
Position monitor					✓**				
Temperature monitor					✓**				
General purpose					✓**				
<b>Built-in Protection</b>									
Current limiter (adjustable)					✓				
Overcurrent					✓				
Thermal motor protection					✓				
Thermal controller protection					✓				
Overvoltage					✓				
Undervoltage					✓				
Voltage transients					✓				
Short-circuit of motor winding					✓				
Loss of feedback signal					✓				
Following error					✓				
Status reporting					✓				
Firmware error handling					✓				
<b>Software</b>									
Installation Program					EPOS Setup				
Graphical User Interface					EPOS Studio				
Startup					✓				
Regulation Tuning					✓				
Diagnostics					✓**				
Firmware Update					✓				
Motion Commander					✓				
I/O Monitor					✓				
Parameters					✓				
Data Recording					✓				
Command Analyzer					✓				
CANopen Wizard					✓				
Online Help					✓				
Language					English				
Operating System					Windows 10, 8, 7				
Windows DLL for PC					32-bit / 64-bit				
PC master					IXXAT, National Instruments, NI-XNET, Kvaser, Vector				
Programming examples					Microsoft Visual Basic, Visual Basic.NET, Visual C#, Visual C++ Borland C++, Delphi National Instruments LabView, LabWindows/CVI				
Linux Shard Object Library					X86 32-Bit/64-Bit, ARMv7				
Programming examples					Eclipse C++/QT				
IEC 61131-3 library for CAN master					Beckhoff**				
maxon library for NI SoftMotion					National Instruments Compact Rio**				

	EPOS4 Module 24/1.5 (536630)	EPOS4 Compact 24/1.5 CAN (546714)	EPOS4 50/5 (546047)	EPOS4 Module 50/5 (534130)	EPOS4 Compact 50/5 CAN (541718)	EPOS4 Module 50/8 (504384)	EPOS4 Compact 50/8 CAN (520885)	EPOS4 Module 50/15 (504383)	EPOS4 Compact 50/15 CAN (520886)
<b>Accessories (not included in delivery)</b>									
520858	CAN-CAN Cable	—	✓	✓	—	✓	—	✓	—
520857	CAN-COM Cable	—	✓	✓	—	✓	—	✓	—
275934	Encoder Cable	—	✓	✓	—	✓	—	✓	—
422827	Ethernet Cable	—	—	✓	—	—	—	—	—
275878	Hall Sensor Cable	—	—	✓	—	✓	—	✓	—
520854	Signal Cable 7core	—	✓	✓	—	✓	—	✓	—
520853	Signal Cable 8core	—	✓	✓	—	✓	—	✓	—
275851	Motor Cable	—	—	✓	—	✓	—	✓	—
520851	Motor Cable High Current	—	—	—	—	—	—	—	✓
275829	Power Cable	—	—	✓	—	—	✓ (b)	—	✓ (b)
520850	Power Cable High Current	—	—	—	—	—	✓ (c)	—	✓ (c)
520856	RS232-COM Cable	—	✓	✓	—	✓	—	✓	—
520852	Sensor Cable 5x2core	—	✓	✓	—	✓	—	✓	—
520860	STO Idle Connector X9	—	✓ (included)	✓ (included)	—	✓ (included)	—	✓ (included)	—
403968	USB Type A - micro B Cable	✓	✓	✓	✓	✓	✓	✓	✓
536997	EPOS4 CB 24/1.5 CAN	✓	—	—	—	—	—	—	—
534133	EPOS4 CB 50/5 CAN	—	—	—	✓	—	—	—	—
520884	EPOS4 CB Power CAN	—	—	—	—	✓	—	✓	—
520859	EPOS4 Connector Set	—	✓	✓	—	✓	—	✓	—

In the present document, registered brand names are not tagged with their respective trademark. It must be understood that the brands (below list is not necessarily concluding) are protected by copyright and/or other intellectual property rights even if their legal trademarks are omitted.

- BiSS © iC-Haus GmbH, DE-Bodenheim
- Borland®, Borland C++ © Borland Software Corporation, USA-Rockville MD
- CANopen®, CiA® © CiA CAN in Automation e.V., DE-Nuremberg
- CLIK-Mate™, Micro-Fit™, Mini-Fit Jr.™, Mega-Fit® © Molex, USA-Lisle, IL
- Eclipse™ © Eclipse Foundation, Inc., CDN-Ottawa ON
- EnDat © DR. JOHANNES HEIDENHAIN GmbH, DE-Traunreut
- EtherCAT® © EtherCAT Technology Group, DE-Nuremberg, licensed by Beckhoff Automation GmbH, DE-Verl
- har-flexicon® © HARTING AG & Co. KG, DE-Espelkamp
- LabVIEW™, LabWindows™, NI SoftMotion™ © National Instruments Corporation, USA-Austin TX
- Linux® © Linus Torvalds (The Linux Foundation, USA-San Francisco CA)
- Minimodul © Lumberg Holding GmbH & Co. KG, DE-Schalksmühle
- NI-XNET™ © National Instruments Corporation, USA-Austin TX
- PCI Express®, PCIe® © PCI-SIG, USA-Beaverton, OR
- Visual Basic®, Visual C#®, Visual C++®, Windows® © Microsoft Corporation, USA-Redmond WA