

maxon motor control's EPOS4 products are small-sized, full digital, smart positioning control units. Their high power density allows flexible use for brushed DC and brushless EC (BLDC) motors up to approximately 1'050 Watts with various feedback options, such as Hall sensors, incremental encoders as well as absolute sensors in a multitude of drive applications.

EPOS4 controllers are specially designed to be commanded and controlled as a slave node in the CANopen network. In addition, the units can be operated via any USB or RS232 communication port of a Windows or Linux workstation. Moreover, the integrated extension interface allows optional communication interfaces, such as EtherCAT or other additional functionalities.

Latest technology, such as field-oriented control (FOC) and acceleration/velocity feed forward in combination with highest control cycle rates allow sophisticated, ease-of-use motion control.

Legend: ✓ = included / (✓) = on request / nnnnnn = order number / ** = available shortly / (a) requires an optionally available extension card (see "Accessories" on page 7) / (b) optional for separate logic supply / (c) mandatory for supply of power stage / (d) with suitable motherboard



epos.maxonmotor.com


	EPOS4 Module 24/1.5			EPOS4 Module 50/5		EPOS4 Module 50/8			EPOS4 Module 50/15			EPOS4 70/15 (594385)
	Module 24/1.5 (536630)	Compact 24/1.5 CAN (546714)	EPOS4 50/5 (546047)	Module 50/5 (534130)	Compact 50/5 CAN (541718)	Module 50/8 (504384)	Compact 50/8 CAN (520885)	Compact 50/8 EtherCAT (605298)	Module 50/15 (504383)	Compact 50/15 CAN (520886)	Compact 50/15 EtherCAT (605299)	
<p>for comparison purposes: US Half Dollar coin (Ø30.6 mm)</p>												
Communication Interfaces												
CANopen Slave	max. 1 Mbit/s	max. 1 Mbit/s	max. 1 Mbit/s	max. 1 Mbit/s	max. 1 Mbit/s	max. 1 Mbit/s	max. 1 Mbit/s	—	max. 1 Mbit/s	max. 1 Mbit/s	—	max. 1 Mbit/s
CANopen Application Layer and Communication Profile	CiA 301	CiA 301	CiA 301	CiA 301	CiA 301	CiA 301	CiA 301	—	CiA 301	CiA 301	—	CiA 301
CANopen Layer Setting Services and Protocol (LSS)	CiA 305**	CiA 305**	CiA 305**	CiA 305**	CiA 305**	CiA 305**	CiA 305**	—	CiA 305**	CiA 305**	—	CiA 305**
CANopen Device Profile Drives and Motion Control	CiA 402	CiA 402	CiA 402	CiA 402	CiA 402	CiA 402	CiA 402	—	CiA 402	CiA 402	—	CiA 402
USB 2.0 / USB 3.0	Full speed											
Gateway function USB-to-CAN	✓	✓	✓	✓	✓	✓	✓	—	✓	✓	—	✓
RS232	max. 115'200 bit/s	max. 115'200 bit/s	max. 115'200 bit/s	max. 115'200 bit/s	max. 115'200 bit/s	max. 115'200 bit/s	max. 115'200 bit/s	—	max. 115'200 bit/s	max. 115'200 bit/s	—	max. 115'200 bit/s
Gateway function RS232-to-CAN	✓	✓	✓	✓	✓	✓	✓	—	✓	✓	—	✓
EtherCAT Slave	✓ (a)	—	✓ (a)	✓ (a)	—	✓ (a)	—	✓	✓ (a)	—	✓	✓ (a)
IEC 61158 Digital data communication for measurement and control Fieldbus for use in industrial control systems	Type 12 (EtherCAT) max. 100 Mbit/s (100 Base Tx)	—	Type 12 (EtherCAT) max. 100 Mbit/s (100 Base Tx)	Type 12 (EtherCAT) max. 100 Mbit/s (100 Base Tx)	—	Type 12 (EtherCAT) max. 100 Mbit/s (100 Base Tx)	—	Type 12 (EtherCAT) max. 100 Mbit/s (100 Base Tx)	Type 12 (EtherCAT) max. 100 Mbit/s (100 Base Tx)	—	Type 12 (EtherCAT) max. 100 Mbit/s (100 Base Tx)	Type 12 (EtherCAT) max. 100 Mbit/s (100 Base Tx)
IEC 61800-7 Generic interface and use of profiles for power drive systems	Profile type 1 (CiA 402)	—	Profile type 1 (CiA 402)	Profile type 1 (CiA 402)	—	Profile type 1 (CiA 402)	—	Profile type 1 (CiA 402)	Profile type 1 (CiA 402)	—	Profile type 1 (CiA 402)	Profile type 1 (CiA 402)
CAN application layer over EtherCAT (CoE)	✓	—	✓	✓	—	✓	—	✓	✓	—	✓	✓
File transfer over EtherCAT (FoE)	✓**	—	✓**	✓**	—	✓**	—	✓**	✓**	—	✓**	✓**
Distributed clocks support	✓	—	✓	✓	—	✓	—	✓	✓	—	✓	✓
Cyclic modes support cycle times down to...	1 ms	—	1 ms	1 ms	—	1 ms	—	1 ms	1 ms	—	1 ms	1 ms
Process data	PDO mapping (Variable)	—	PDO mapping (Variable)	PDO mapping (Variable)	—	PDO mapping (Variable)	—	PDO mapping (Variable)	PDO mapping (Variable)	—	PDO mapping (Variable)	PDO mapping (Variable)
Motors												
Brushed DC motors up to (continuous / max.)	36 W / 108 W	36 W / 108 W	250 W / 750 W	250 W / 750 W	250 W / 750 W	400 W / 1'500 W	400 W / 1'500 W	400 W / 1'500 W	750 W / 1'500 W	750 W / 1'500 W	750 W / 1'500 W	1050 W / 2100 W
Brushless EC motors (BLDC) up to (continuous / max.)	36 W / 108 W	36 W / 108 W	250 W / 750 W	250 W / 750 W	250 W / 750 W	400 W / 1'500 W	400 W / 1'500 W	400 W / 1'500 W	750 W / 1'500 W	750 W / 1'500 W	750 W / 1'500 W	1050 W / 2100 W

	EPOS4 Module 24/1.5		EPOS4 50/5 (546047)	EPOS4 Module 50/5		EPOS4 Module 50/8			EPOS4 Module 50/15			EPOS4 70/15 (594385)
	Module 24/1.5 (536630)	Compact 24/1.5 CAN (546714)		Module 50/5 (534130)	Compact 50/5 CAN (541718)	Module 50/8 (504384)	Compact 50/8 CAN (520885)	Compact 50/8 EtherCAT (605298)	Module 50/15 (504383)	Compact 50/15 CAN (520886)	Compact 50/15 EtherCAT (605299)	
Sensors (Feedback)												
Digital Hall sensors (EC motors)	✓											
Digital incremental encoder (2-/3-channel, single-ended or differential)	✓											
Analog incremental encoder (3-channel, sin/cos, differential)	✓											
SSI absolute encoder (configurable)	✓											
BiSS C absolute encoder (configurable)	(✓) (a)	—	(✓) (a)	(✓) (a)	—	(✓) (a)	—	—	(✓) (a)	—	—	(✓) (a)
EnDat 2.2 absolute encoder (configurable)	(✓) (a)	—	(✓) (a)	(✓) (a)	—	(✓) (a)	—	—	(✓) (a)	—	—	(✓) (a)
Commutation												
Digital Hall sensors	✓											
Digital Hall sensors + digital incremental encoder	✓											
Digital Hall sensors + analog incremental encoder	✓											
Digital Hall sensors + absolute encoder	✓											
Absolute encoder	✓											
Electrical Data												
Nominal power supply voltage (+V _{CC})	10...24 VDC	10...24 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...70 VDC
Nominal logic supply voltage (+V _C)	10...24 VDC	10...24 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...70 VDC
Absolute supply voltage limits (+V _{min} / +V _{max})	8 VDC / 28 VDC	8 VDC / 28 VDC	8 VDC / 56 VDC	8 VDC / 56 VDC	8 VDC / 56 VDC	8 VDC / 56 VDC	8 VDC / 56 VDC	8 VDC / 56 VDC	8 VDC / 56 VDC	8 VDC / 56 VDC	8 VDC / 56 VDC	8 VDC / 75 VDC
Output voltage (max.)	0.9 x +V _{CC}											
Output current (I _{cont} / I _{max})	1.5 A / 4.5 A (<30 s)	1.5 A / 4.5 A (<30 s)	5 A / 15 A (<15s)	5 A / 15 A (<3 s)	5 A / 15 A (<3 s)	8 A / 30 A (<5 s)	8 A / 30 A (<5 s)	8 A / 30 A (<5 s)	15 A / 30 A (<60 s)	15 A / 30 A (<60 s)	15 A / 30 A (<60 s)	15 A / 30 A (<60 s)
Pulse width modulation frequency	100 kHz	100 kHz	50 kHz	50 kHz	50 kHz	50 kHz	50 kHz	50 kHz	50 kHz	50 kHz	50 kHz	50 kHz
Sampling rate PI current controller	25 kHz (40 μs)											
Sampling rate PID speed controller	2.5 kHz (400 μs)											
Sampling rate PID positioning controller	2.5 kHz (400 μs)											
Max. efficiency	89%	89%	98%	97%	97%	98%	98%	98%	98%	98%	98%	98%
Max. speed DC motor	limited by max. permissible speed (motor)											
Max. speed EC motor, block commutation	100'000 rpm (1 pole pair)											
Max. speed EC motor, sinusoidal commutation	50'000 rpm (1 pole pair)											
Built-in motor choke	—	3 x 94 μH; 1.5 A	3 x 15 μH; 5 A	—	3 x 9.4 μH; 5 A	—	3 x 2.2 μH; 15 A	3 x 2.2 μH; 15 A	—	3 x 2.2 μH; 15 A	3 x 2.2 μH; 15 A	3 x 15 μH; 15 A
Inputs / Outputs												
Digital Hall sensor signals	H1, H2, H3 (+2...+24 VDC, internal pull-up)											
Digital incremental encoder signals	A, A\, B, B\, I, I\ (EIA RS422, 6.25 MHz)											
Encoder signals	A, A\, B, B\, I, I\ (EIA RS422, 6.25 MHz) Clock, Clock\ Data, Data\ 4 (+2.1...+36 VDC)											
Digital inputs	all Modules	4; level selectable by DIP switch: (Logic level: +2.0...+30 VDC) or (PLC level: +9.0...+30 VDC)										
Digital outputs	all Compacts and housing versions	2 (open collector, max. 36 VDC / 500 mA, internal pull-up)										
High-speed digital inputs	4 (EIA RS422, 6.25 MHz)											
High-speed digital outputs	1 (EIA RS422, 6.25 MHz)											
Analog inputs	2 (resolution 12-bit, -10...+10 V, 10 kHz, differential)											

		EPOS4 Module 24/1.5		EPOS4 50/5 (546047)	EPOS4 Module 50/5		EPOS4 Module 50/8			EPOS4 Module 50/15			EPOS4 70/15 (594385)			
		Module 24/1.5 (536630)	Compact 24/1.5 CAN (546714)		Module 50/5 (534130)	Compact 50/5 CAN (541718)	Module 50/8 (504384)	Compact 50/8 CAN (520885)	Compact 50/8 EtherCAT (605298)	Module 50/15 (504383)	Compact 50/15 CAN (520886)	Compact 50/15 EtherCAT (605299)				
Analog outputs		2 (resolution 12-bit, -4...+4 V, 25 kHz)														
STO inputs		2 (+4.5...+30 VDC, optically isolated)														
STO outputs		1 (max. 30 VDC / 15 mA, optically isolated with self-resetting short-circuit protection)														
Sensor supply voltage		+5 VDC (I _L ≤100 mA)														
Auxiliary output voltage		+5 VDC (I _L ≤150 mA)														
		Device status														
Status indicators (LEDs or bi-color LEDs)		—	—	NET status	—	—	—	—	NET status	—	—	NET status	NET status			
		—	—	NET port	—	—	—	—	NET port	—	—	NET port	NET port			
Connections																
X1	Power Supply	Box header 1.27 mm pitch 2x23 poles	—	Molex Mini-Fit Jr. 2 poles	Box header 1.27 mm pitch 2x23 poles	—	Pin header 2.54 mm pitch 2x16 poles	Molex Mega-Fit 2 poles	Molex Mega-Fit 2 poles	Pin header 2.54 mm pitch 2x16 poles	Molex Mega-Fit 2 poles	Molex Mega-Fit 2 poles	Molex Mega-Fit 2 poles			
X2	Logic Supply		—	Molex Mini-Fit Jr. 2 poles		—		Molex Mini-Fit Jr. 2 poles	Molex Mini-Fit Jr. 2 poles		Molex Mini-Fit Jr. 2 poles	Molex Mini-Fit Jr. 2 poles	Molex Mini-Fit Jr. 2 poles	Molex Mini-Fit Jr. 2 poles	Molex Mini-Fit Jr. 2 poles	Molex Mini-Fit Jr. 2 poles
X1/X2	Power & Logic Supply		Harting har-flexicon 3 poles	—		Harting har-flexicon 3 poles		—	—		—	—	—	—	—	—
X3	Motor		—	Molex Mini-Fit Jr. 4 poles		Molex Mini-Fit Jr. 4 poles		—	—		—	—	—	—	—	—
X3a	Motor (I _{cont} ≤11 A)		—	—		—		Molex Mini-Fit Jr. 4 poles	Molex Mini-Fit Jr. 4 poles		—	—	—	Molex Mini-Fit Jr. 4 poles	Molex Mini-Fit Jr. 4 poles	Molex Mini-Fit Jr. 4 poles
X3b	Motor (I _{cont} ≤15 A)		—	—		—		—	—		—	—	—	Molex Mega-Fit 4 poles	Molex Mega-Fit 4 poles	Molex Mega-Fit 4 poles
X3c	Motor		Hirose DF3DZ 3 poles	—		—		—	—		—	—	—	—	—	—
X3a/X4a	Motor & Hall Sensor		Harting har-flexicon 8 poles	—		—		—	—		—	—	—	—	—	—
X3b/X4b	Motor & Hall Sensor		Lumberg Minimodule 8 poles	—		—		—	—		—	—	—	—	—	—
X4	Hall Sensor		—	Molex Micro-Fit 3.0 6 poles		Molex Micro-Fit 3.0 6 poles		—	—		Molex Micro-Fit 3.0 6 poles	Molex Micro-Fit 3.0 6 poles	—	Molex Micro-Fit 3.0 6 poles	Molex Micro-Fit 3.0 6 poles	Molex Micro-Fit 3.0 6 poles
X5	Encoder	Pin header 2.54 mm pitch 2x5 poles	Pin header 2.54 mm pitch 2x5 poles	Pin header 2.54 mm pitch 2x5 poles	Pin header 2.54 mm pitch 2x5 poles	Pin header 2.54 mm pitch 2x5 poles	Pin header 2.54 mm pitch 2x5 poles	Pin header 2.54 mm pitch 2x5 poles	Pin header 2.54 mm pitch 2x5 poles	Pin header 2.54 mm pitch 2x5 poles	Pin header 2.54 mm pitch 2x5 poles	Pin header 2.54 mm pitch 2x5 poles	Pin header 2.54 mm pitch 2x5 poles			
X6	Sensor	Box header 1.27 mm pitch 2x23 poles	Molex CLIK-Mate 2x5 poles	Molex CLIK-Mate 2x5 poles	Box header 1.27 mm pitch 2x23 poles	Molex CLIK-Mate 2x5 poles	Pin header 2.54 mm pitch 2x23 poles	Molex CLIK-Mate 2x5 poles	Molex CLIK-Mate 2x5 poles	Pin header 2.54 mm pitch 2x23 poles	Molex CLIK-Mate 2x5 poles	Molex CLIK-Mate 2x5 poles	Molex CLIK-Mate 2x5 poles			
X7	Digital I/O		Molex CLIK-Mate 8 poles	Molex CLIK-Mate 8 poles		Molex CLIK-Mate 8 poles		Molex CLIK-Mate 8 poles	Molex CLIK-Mate 8 poles		Molex CLIK-Mate 8 poles	Molex CLIK-Mate 8 poles	Molex CLIK-Mate 8 poles	Molex CLIK-Mate 8 poles	Molex CLIK-Mate 8 poles	Molex CLIK-Mate 8 poles
X8	Analog I/O		Molex CLIK-Mate 7 poles	Molex CLIK-Mate 7 poles		Molex CLIK-Mate 7 poles		Molex CLIK-Mate 7 poles	Molex CLIK-Mate 7 poles		Molex CLIK-Mate 7 poles	Molex CLIK-Mate 7 poles	Molex CLIK-Mate 7 poles	Molex CLIK-Mate 7 poles	Molex CLIK-Mate 7 poles	Molex CLIK-Mate 7 poles
X9	STO		Molex CLIK-Mate 8 poles	Molex CLIK-Mate 8 poles		Molex CLIK-Mate 8 poles		Molex CLIK-Mate 8 poles	Molex CLIK-Mate 8 poles		Molex CLIK-Mate 8 poles	Molex CLIK-Mate 8 poles	Molex CLIK-Mate 8 poles	Molex CLIK-Mate 8 poles	Molex CLIK-Mate 8 poles	Molex CLIK-Mate 8 poles
X10	RS232		Molex CLIK-Mate 5 poles	Molex CLIK-Mate 5 poles		Molex CLIK-Mate 5 poles		Molex CLIK-Mate 5 poles	Molex CLIK-Mate 5 poles		—	—	—	Molex CLIK-Mate 5 poles	—	Molex CLIK-Mate 5 poles
X11	CAN 1		Molex CLIK-Mate 4 poles	Molex CLIK-Mate 4 poles		Molex CLIK-Mate 4 poles		Molex CLIK-Mate 4 poles	Molex CLIK-Mate 4 poles		—	—	—	Molex CLIK-Mate 4 poles	—	Molex CLIK-Mate 4 poles
X12	CAN 2		Molex CLIK-Mate 4 poles	Molex CLIK-Mate 4 poles		Molex CLIK-Mate 4 poles		Molex CLIK-Mate 4 poles	Molex CLIK-Mate 4 poles		—	—	—	Molex CLIK-Mate 4 poles	—	Molex CLIK-Mate 4 poles
X13	USB	USB Type micro B, female														
X14	Extension IN (a)	—	—	RJ45 10/100- BASE-TX	—	—	—	—	RJ45 10/100- BASE-TX	—	—	RJ45 10/100- BASE-TX	RJ45 10/100- BASE-TX			

	EPOS4 Module 24/1.5		EPOS4 50/5 (546047)	EPOS4 Module 50/5		EPOS4 Module 50/8			EPOS4 Module 50/15			EPOS4 70/15 (594385)
	Module 24/1.5 (536630)	Compact 24/1.5 CAN (546714)		Module 50/5 (534130)	Compact 50/5 CAN (541718)	Module 50/8 (504384)	Compact 50/8 CAN (520885)	Compact 50/8 EtherCAT (605298)	Module 50/15 (504383)	Compact 50/15 CAN (520886)	Compact 50/15 EtherCAT (605299)	
X15 Extension OUT (a)	—	—	RJ45 10/100-BASE-TX	—	—	—	—	RJ45 10/100-BASE-TX	—	—	RJ45 10/100-BASE-TX	RJ45 10/100-BASE-TX
X16 Extension Signal (a)	—	—	Molex CLIK-Mate 2x5 poles	—	—	—	—	—	—	—	—	Molex CLIK-Mate 2x5 poles
Mechanical Data												
Weight (approximate)	17 g	58 g	206 g	17 g	58 g	23 g	86 g	100 g	70 g	126 g	140 g	372 g
Dimensions (L x W x H) [mm]	53.8 x 38.8 x 11.1	55.0 x 40.0 x 31.1	105.0 x 83.0 x 38.7	53.8 x 38.8 x 11.1	55.0 x 40.0 x 31.1	59.5 x 46.0 x 14.1	59.5 x 58.5 x 33.0	59.5 x 79.5 x 35.7	59.5 x 62.0 x 16.4	59.5 x 65.5 x 35.1	59.5 x 79.5 x 37.8	125.0 x 94.5 x 38.7
Mounting	Pluggable (female headers 1.27 mm) or M2.5 screws	M2.5 screws	M4 screws	Pluggable (female headers 1.27 mm) or M2.5 screws	M2.5 screws	Pluggable (female headers 2.54 mm) or M2.5 screws	M2.5 screws	M2.5 screws	Pluggable (female headers 2.54 mm) or M3 screws	M3 screws	M3 screws	M4 screws
Environmental Conditions												
Temperature – Operation	-30...+60 °C	-30...+45 °C	-30...+50 °C	-30...+45 °C	-30...+25 °C	-30...+45 °C	-30...+45 °C	-30...+45 °C	-30...+25 °C	-30...+25 °C	-30...+25 °C	-30...+50 °C
Temperature – Extended range and derating	+60...+73 °C -0.115 A/°C	+45...+70 °C -0.060 A/°C	+50...+80 °C -0.167 A/°C	+45...+75 °C -0.167 A/°C	+25...+70 °C -0.111 A/°C	+45...+77 °C -0.250 A/°C	+45...+77 °C -0.250 A/°C	+45...+77 °C -0.250 A/°C	+25...+77 °C -0.288 A/°C	+25...+77 °C -0.288 A/°C	+25...+77 °C -0.288 A/°C	+50...+85 °C -0.429 A/°C
Temperature – Storage	-40...+85 °C											
Altitude – Operation	0...6'000 m MSL											
Altitude – Extended range	6'000...10'000 m MSL (for derating see Hardware Reference)											
Humidity (condensation not permitted)	5...90%											
Directives & Standards												
Generic	IEC/EN 61000-6-2; IEC/EN 61000-6-3											
Applied	IEC/EN 55022 (CISPR22); IEC/EN 61000-4-3; IEC/EN 61000-4-4; IEC/EN 61000-4-6											
Environment	IEC/EN 60068-2-6; MIL-STD-810F											
Safety (UL File Number; unassembled PCB)	E207844	E207844	E229342	E207844	E207844	E76251; E207844; E337862	E76251; E116354; E207844; E337862	E76251; E207844; E337862; E133472	E76251; E207844; E337862	E76251; E116354; E207844; E337862	E76251; E207844; E337862; E133472	E207844
Reliability (MIL-HDBK-217F; MTBF)	611'610 hours	326'977 hours	296'741 hours	314'822 hours	253'865 hours	245'451 hours	210'109 hours	197'129 hours	240'400 hours, with heat sink <3.1 K/W	199'049 hours, with heat sink <3.1 K/W	179'777 hours, with heat sink <3.1 K/W	254'446 hours
Functionality												
Operating Modes												
CST Cyclic Synchronous Torque Mode	✓											
CSV Cyclic Synchronous Velocity Mode	✓											
CSP Cyclic Synchronous Position Mode	✓											
PVM Profile Velocity Mode	✓											
PPM Profile Position Mode	✓											
IPM Interpolated Position Mode	(✓)											
HMM Homing Mode	✓											
Master Encoder Functionality	(✓)											
Step/Direction Functionality	(✓)											
Analog Set Value Functionality	✓**											
Features												
Feed forward (acceleration/velocity for inertia and friction compensation)	✓											
Field-oriented Control (FOC)	✓											
Velocity observer	✓											
Standalone programmability	(✓)											
Custom persistent memory	✓											

	EPOS4 Module 24/1.5		EPOS4 50/5 (546047)	EPOS4 Module 50/5		EPOS4 Module 50/8			EPOS4 Module 50/15			EPOS4 70/15 (594385)	
	Module 24/1.5 (536630)	Compact 24/1.5 CAN (546714)		Module 50/5 (534130)	Compact 50/5 CAN (541718)	Module 50/8 (504384)	Compact 50/8 CAN (520885)	Compact 50/8 EtherCAT (605298)	Module 50/15 (504383)	Compact 50/15 CAN (520886)	Compact 50/15 EtherCAT (605299)		
Advanced automatic control settings (Auto Tuning)													✓
Safe Torque Off (based on IEC/EN 61800-5-2, certification pending)													✓
Digital I/O Functionality													
Inputs (configurable)													✓
Touch Probe													(✓)
Reference switches													✓
Limit switches													✓
Quickstop													✓
Drive Enable													✓
General purpose													✓
Outputs (configurable)													✓
Position Compare													(✓)
Holding Brake													✓
Ready/Fault													✓
General purpose													✓
Analog I/O Functionality													
Inputs (configurable)													✓
Analog set value													✓**
General purpose													✓
Outputs (configurable)													✓**
Current monitor													✓**
Velocity monitor													✓**
Position monitor													✓**
Temperature monitor													✓**
General purpose													✓**
Built-in Protection													
Current limiter (adjustable)													✓
Overcurrent													✓
Thermal motor protection													✓
Thermal controller protection													✓
Overvoltage													✓
Undervoltage													✓
Voltage transients													✓
Short-circuit of motor winding													✓
Loss of feedback signal													✓
Following error													✓
Status reporting													✓
Firmware error handling													✓

	EPOS4 Module 24/1.5		EPOS4 50/5 (546047)	EPOS4 Module 50/5		EPOS4 Module 50/8			EPOS4 Module 50/15			EPOS4 70/15 (594385)
	Module 24/1.5 (536630)	Compact 24/1.5 CAN (546714)		Module 50/5 (534130)	Compact 50/5 CAN (541718)	Module 50/8 (504384)	Compact 50/8 CAN (520885)	Compact 50/8 EtherCAT (605298)	Module 50/15 (504383)	Compact 50/15 CAN (520886)	Compact 50/15 EtherCAT (605299)	
Software												
Installation Program	EPOS Setup											
Graphical User Interface	EPOS Studio											
												
	The EPOS video library features video tutorials that provide easy to follow instructions on how to get started with «EPOS Studio» and shows you tips and tricks on how to setup communication interfaces, motors and sensors, and so on. Explore on Vimeo: → https://vimeo.com/album/4646388											
Startup	✓											
Regulation Tuning	✓											
Firmware Update	✓											
Motion Commander	✓											
I/O Monitor	✓											
Parameters	✓											
Data Recording	✓											
Command Analyzer	✓											
CANopen Wizard	✓											
Online Help	✓											
Language	English											
Operating System	Windows 10, 8, 7											
Windows DLL for PC	32-bit / 64-bit											
CAN interfaces	IXXAT National Instruments Kvaser Vector											
Programming examples	Microsoft Visual Basic, Visual Basic.NET, Visual C#, Visual C++ Borland C++, Delphi National Instruments LabView, LabWindows/CVI											
Linux Shared Object Library	X86 32-bit/64-bit, ARMv7/v8 32-bit											
CAN interfaces	IXXAT Kvaser											
Programming examples	C++											

		EPOS4 Module 24/1.5		EPOS4 50/5 (546047)	EPOS4 Module 50/5		EPOS4 Module 50/8			EPOS4 Module 50/15			EPOS4 70/15 (594385)
		Module 24/1.5 (536630)	Compact 24/1.5 CAN (546714)		Module 50/5 (534130)	Compact 50/5 CAN (541718)	Module 50/8 (504384)	Compact 50/8 CAN (520885)	Compact 50/8 EtherCAT (605298)	Module 50/15 (504383)	Compact 50/15 CAN (520886)	Compact 50/15 EtherCAT (605299)	
Accessories (not included in delivery)													
520858	CAN-CAN Cable	—	✓	✓	—	✓	—	✓	—	—	✓	—	✓
520857	CAN-COM Cable	—	✓	✓	—	✓	—	✓	—	—	✓	—	✓
275934	Encoder Cable	—	✓	✓	—	✓	—	✓	✓	—	✓	✓	✓
422827	Ethernet Cable	—	—	✓	—	—	—	—	✓	—	—	✓	✓
275878	Hall Sensor Cable	—	—	✓	—	✓	—	✓	✓	—	✓	✓	✓
520854	Signal Cable 7core	—	✓	✓	—	✓	—	✓	✓	—	✓	✓	✓
520853	Signal Cable 8core	—	✓	✓	—	✓	—	✓	✓	—	✓	✓	✓
275851	Motor Cable	—	—	✓	—	✓	—	✓	✓	—	✓	✓	✓
520851	Motor Cable High Current	—	—	—	—	—	—	—	—	—	✓	✓	✓
275829	Power Cable	—	—	✓	—	—	—	✓ (b)	✓ (b)	—	✓ (b)	✓ (b)	✓ (b)
520850	Power Cable High Current	—	—	—	—	—	—	✓ (c)	✓ (c)	—	✓ (c)	✓ (c)	✓ (c)
520856	RS232-COM Cable	—	✓	✓	—	✓	—	✓	—	—	✓	—	✓
520852	Sensor Cable 5x2core	—	✓	✓	—	✓	—	✓	✓	—	✓	✓	✓
520860	STO Idle Connector X9	—	✓ (included)	✓ (included)	—	✓ (included)	—	✓ (included)	✓ (included)	—	✓ (included)	✓ (included)	✓ (included)
403968	USB Type A - micro B Cable	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
536997	EPOS4 CB 24/1.5 CAN	✓	—	—	—	—	—	—	—	—	—	—	—
534133	EPOS4 CB 50/5 CAN	—	—	—	✓	—	—	—	—	—	—	—	—
520884	EPOS4 CB Power CAN	—	—	—	—	—	✓	—	—	✓	—	—	—
604594	EPOS4 CB Power EtherCAT	—	—	—	—	—	✓	—	—	✓	—	—	—
520859	EPOS4 Connector Set	—	✓	✓	—	✓	—	✓	✓	—	✓	✓	✓
581245	EPOS4 EtherCAT Card	✓ (d)	—	✓	✓ (d)	—	✓ (d)	—	—	✓ (d)	—	—	✓

In the present document, registered brand names are not tagged with their respective trademark. It must be understood that the brands (below list is not necessarily concluding) are protected by copyright and/or other intellectual property rights even if their legal trademarks are omitted.

- BiSS © iC-Haus GmbH, DE-Bodenheim
- Borland®, Borland C++ © Borland Software Corporation, USA-Rockville MD
- CANopen®, CiA® © CiA CAN in Automation e.V., DE-Nuremberg
- CLIK-Mate™, Micro-Fit™, Mini-Fit Jr.™, Mega-Fit® © Molex, USA-Lisle, IL
- Eclipse™ © Eclipse Foundation, Inc., CDN-Ottawa ON
- EnDat © DR. JOHANNES HEIDENHAIN GmbH, DE-Traunreut
- EtherCAT® © EtherCAT Technology Group, DE-Nuremberg, licensed by Beckhoff Automation GmbH, DE-Verl
- har-flexicon® © HARTING AG & Co. KG, DE-Espelkamp
- LabVIEW™, LabWindows™, NI SoftMotion™ © National Instruments Corporation, USA-Austin TX
- Linux® © Linus Torvalds (The Linux Foundation, USA-San Francisco CA)
- Minimodul © Lumberg Holding GmbH & Co. KG, DE-Schalksmühle
- NI-XNET™ © National Instruments Corporation, USA-Austin TX
- PCI Express®, PCIe® © PCI-SIG, USA-Beaverton, OR
- Visual Basic®, Visual C#®, Visual C++®, Windows® © Microsoft Corporation, USA-Redmond WA